

# BC1500 BRUSH CHIPPER



**CHIPPING PRODUCTIVITY.** The SmartFeed system monitors engine rpm and automatically stops and reverses the feed rollers to enhance production. This system also senses feed roller jams and manipulates the material automatically to reduce the need for manual control bar use.



**EASILY LIFT HEAVY MATERIAL.** An optional winch allows operators to move large logs effortlessly. The 150' (45.7 m) winch line can handle logs up to 2000 lb (907.2 kg) and can automatically lift the logs onto the feed table.



**OPERATOR SAFETY.** Mounted over the feed table, the four-position upper feed control bar enables the operator to stop the feed rollers and select forward/reverse. The patented bottom feed stop bar is strategically located to make it possible for an operator's leg to strike the bar and shut off the feed mechanism either intentionally or automatically in an emergency situation.



**TAKE CONTROL.** With the standard Tree Commander™ remote control, jobsite productivity is improved by allowing the operator to control brush chipper functions remotely. The remote can be attached to the operator's belt or held in an optional bracket mounted directly to the operator's station of a Vermeer compact utility loader.

## ECOIDLE™

### ECOIDLE™ ENGINE CONTROL SYSTEM.

When the EcoIdle function is selected by the operator, the engine speed automatically lowers to a preset rpm after one or five minutes of inactivity to help reduce fuel consumption when not chipping material. Due to this idling, noise and greenhouse emissions are also reduced.



**SMOOTH FEEDING.** Vertical feed rollers with helical cleats help hold material firmly to the infeed table, which reduces vibration, shock and structural loading to the rear of the machine.

# BC1500 BRUSH CHIPPER

## GENERAL

Length: 179" (454.7 cm)

Height: 104" (264.2 cm)

Width: 86" (218.4 cm)

Weight (without winch): 7490 lb (3397.4 kg)

Weight (with winch): 7770 lb (3524.4 kg)

## ENGINE OPTION ONE

Make/Model: Cummins QSF3.8L Tier 4 Final

Gross horsepower: 130 hp (97 kW)

Max torque: 360 ft-lb (488.1 Nm)

Fuel type: Diesel

Number of cylinders: 4

## ENGINE OPTION TWO (INTERNATIONAL)

Make/Model: John Deere 4045H Tier 3

Gross horsepower: 125 hp (93 kW)

Max torque: 355 ft-lb (481.3 Nm)

Fuel type: Diesel

Number of cylinders: 4

Contact your local Vermeer dealer for engine availability in your region.

## FEED SYSTEM

Chipping capacity: 15" (38.1 cm)

Infeed opening height: 18.3" (46.5 cm)

Infeed opening width: 15.8" (40.1 cm)

Feed roller orientation: Vertical

Feed table height: 32" (81.3 cm)

Max feed speed: 125 fpm (38.1 m/min)

Feed roller diameter: 21" (53.3 cm)

## CUTTING SYSTEM

Drum speed: 2208 rpm

Drum cutting diameter: 23.8" (60.5 cm)

Drum thickness: .375" (.95 cm)

Knives: 2 knives – .625" x 5" x 8" (1.6 cm x 12.7 cm x 20.3 cm)

Engagement system: Automotive-style clutch

## CAPACITIES/ELECTRICAL

Fuel tank: 45 gal (170.3 L)

Max hydraulic flow: 5.5 gpm (20.8 L/min)

DEF tank: 5 gal (18.9 L)

Lights: LED front, rear, side, brake and taillights

## CHASSIS/BRAKES

Frame: .25" (6.4 mm) Z channel, 7" (17.8 cm)

Tires: LT 285/75R16 LR E

Axle/Suspension: Torsion

## DISCHARGE SYSTEM

Discharge height: 104" (264.2 cm)

Degree of rotation: 270°

## OPTIONS

Tree Commander™ remote control

Extended warranty

Special paint

Planned maintenance

Vermeer Confidence Plus® asset protection program

Winch

Hydraulic chute rotate

Vermeer Corporation reserves the right to make changes in engineering, design and specifications; add improvements; or discontinue manufacturing at any time without notice or obligation. Equipment shown is for illustrative purposes only and may display optional accessories or components. Please contact your local Vermeer dealer for more information on machine specifications. Vermeer, the Vermeer logo, Equipped to Do More, Tree Commander, Ecoldle and Vermeer Confidence Plus are trademarks of Vermeer Manufacturing Company in the U.S. and/or other countries. Cummins is a trademark of Cummins Inc. John Deere is a trademark of Deere & Company. © 2017 Vermeer Corporation. All rights reserved. Printed in the U.S.A. Please recycle.

